

ADA-2 Lectern



Sound-Craft Systems' ADA-2 Presenter® lectern offers a stylish yet functional approach to ADA compliance that easily accommodates the mobility-impaired as well as the standing presenter. A conveniently located oversized rocker switch allows movement over a 10" range, adjusting from an ADA-compliant height to a conventional standard lectern height. A spacious work surface provides more than ample space for laptops, notebooks, docking stations, and other presentation material, plus may be removed to access additional space for mounting small peripherals such as wireless receivers, controllers, etc. Seated presenters will appreciate the ease of entry and exit afforded by the oversized access area.



Sound-Craft Systems, Inc.

1584 Petit Jean Mountain Road
Morrliton, Arkansas 72110
phone: 501.727.5476 or 800.643.8747
fax: 501.727.5402
email: sales@sound-craft.com
website: www.sound-craft.com

For room-to-room mobility, the ADA-2 features 3" locking swivel casters that allow easy portability, yet lock it securely in place once positioned. Service access to the motor is provided by means of the removable work surface, while limit switches can be serviced through removal of an access panel.

Long service life is assured through quality wood construction featuring a steel inner frame for extra rigidity. Eight standard wood veneer finishes are offered, as well as custom veneers, custom color matching, and plastic laminates. A wide variety of options are available to further enhance the versatility and functionality of the ADA-2.

Specifications:

Overall dimensions:	Raised - 47.5" W x 47.5" H x 30.75" D Lowered - 47.5" W x 37.25" H x 30.75" D
Work surface dimensions:	45.75" W x 29.75" D
Work surface height:	Adjustable from 31" to 41"
Presenter Access:	34" W x 27.625" H x 20.875" D
Shipping Weight:	400 lbs.

Construction: Butt-joint and lock-mitered all wood construction with steel inner frame.

Finish: Wood veneer standard; high-pressure plastic laminate optional. Work surface finished in Nevamar® charcoal matrix laminate with ARP scratch-resistant coating.

Electro-mechanical: Motor driven screw drive height adjustment with adjustable limit switches.

Motor: 1/25 HP gear reduction type, 115/230 V, 50-60Hz, .61/.38 Amp. 50:1 gear reduction, 67 rpm.

Other: Momentary contact rocker switch; 6' removable CEE power cable.

Available Options include:

- Solid hardwood trim
- Folding shelf
- Custom work surface cutouts
- Task light
- Digital clock
- Duplex power outlet
- Cable port

Your Local Dealer